PFA

Precision Focus Automation

WDI's next generation Precision Focus Automation "PFA" technology includes the world's fastest and most powerful microscopy autofocus sensor. Driven by demand for higher speed, greater accuracy and more flexibility for a wider variety of applications the PFA sensor features significant advancements in optics, imaging, processing and communication.

- _I_ Higher update rate and faster measurements, greater accuracy and repeatability with improved ease of integration
- Fifteen times greater sensitivity, a global shutter and increased speed along with enhanced ability for both laser and video autofocus
- Major improvements in memory, processor power and function as well as adaptability and programmability
- Gigabit Ethernet communication and Linux OS provide greater reliability and enhanced capabilities





Flexibility

Available as stand alone or an integrated solution, PFA sensors may be adapted to virtually any imaging system and application including flat panel display and semiconductor inspection, biomedical imaging and machine vision metrology.



Higher laser shaping, outputs and software make PFA easier integrate mechanically and electrically without the requirement for an external



Speed

Modern optics, imaging processing and coupled with Gigabit **Ethernet** communication create the fastest autofocus solution available today.



Accuracy

A new imaging sensor together with a powerful processor and sophisticated algorithms provide autofocus accuracy to less than 0.25 the objective DOF on samples as thin as 0.3mm.



controller.



PFA FEATURES

- Capable of both laser and video autofocus for demanding applications with a mixture of substrates, patterned surfaces or varying reflectivity
- Advanced surface recognition functionality analyzes, differentiates and permits continuous focus on a specified surface in multilayer samples
- Programmable 16 bit +/- 10V AO range allows easy integration with any 3rd party piezo, linear or DIO controlled Z actuators
- Alignment and Tune Up wizard software make integration and optimization fast and simple
- Diagnostic and performance reporting provide real time analytic and statistical metrics



WDI's new PFA sensor couples the world's fastest most advanced autofocus technology with integrated automation components to create the perfect microscopy system solutions.

PFA SPECIFICATIONS

Feature		Feature	
Structured Light Pattern	Line	Line Processing Method	Dynamically Adjustable ROI
Laser Wavelengths Available	680 nm, 785 nm Power Output		5 mW maximum
Stand Off Distance	300 mm maximum	Sampling Rate	3.5 kHz (ROI Mode 7 kHz)
Static Autofocus Accuracy	± 0.25 Objective DOF or better	Tracking Autofocus Accuracy	± 0.33 Objective DOF or better
Internal Image Sensor	1.3 MP 4.8 μm pixels 200fps	Shutter Type	Low Noise Global Shutter
Internal Processor	Dual Core ARM A9 @ 533 MHz	Memory	512 MB DDR3 & 32 MB Flash
PC Communication	Gigabit Ethernet	Operating System	Linux OS

Objective (NA)	Linear Range (µm)	Capture Range (µm)	3-Sigma Repeatability Error Limits (µm)	Autofocus Speed (ms)
5X/0.14	± 740	± 10000	< 2	< 75
10×/0.28	± 200	± 6000	<	< 65
20X/0.42	± 170	± 2300	< 0.5	< 120
50×/0.55	± 30	± 400	< 0.5	< 120



WDI is a world leader in the design, manufacture, and integration of OEM and complete microscopy automation solutions for the biomedical, metrology, electronics, semiconductor, and flat panel display markets. WDI's success lies in an innovative culture and ability to optimize and adapt our technology to customers' specific requirements by listening to their needs and gaining a deep understanding of their processes, applications and goals. WDI employs over 40 optical, electrical, mechanical and software engineers, as well as scientists, who are dedicated to servicing our customers. We have locations in Canada and Poland, with service centers in Taiwan and South Korea. Contact WDI today to see how we can help solve your microscopy automation needs.





sales@wdidevice.com



www.wdidevice.com



© 2019 WDI Wise Device Inc. All rights reserved. Design, features, and specifications are subject to change without notice.